

TECHNICAL DATA

Product type	Reverse osmosis watermaker
Application	Seawater for nautical application
Production	100 l/h $\pm 15\%$ (26,4 gal/h $\pm 15\%$) @35 ppm e 25 °C
Membranes	2x Membrane SW-4021
Rejection	99,5% (nominal)
Power supply	12 V $\pm 15\%$ DC 24 V $\pm 15\%$ DC 230 V $\pm 15\%$ AC - 50/60 Hz
Absorption - Power required	36 A $\pm 15\%$ - 400 W $\pm 15\%$ (12 V) 16 A $\pm 15\%$ - 400 W $\pm 15\%$ (24 V) 2,5 A $\pm 15\%$ - 600 W $\pm 15\%$ (230 V)
Pumps	Rotary pump
Pressure pump	7-8 bar
Flow rate pump	15,6 – 16,6 l/min
Water inlet temperature range	8 - 30 °C
Pre-filtration	1x 5micron filter 10"x2-1/2" 1x Active carbon filter 2-7/8" x 9-3/4"



HYDRAULIC CONNECTIONS

PUMP / FILTERS / NR VALVE

Seawater inlet	Hose barb DN20/22 - DN20
Seawater outlet	Hose barb DN20/22 - DN20

WATERMAKER


Seawater inlet	Hose barb DN20/22
Concentrated water outlet	Hose barb DN16
Fresh water outlet	Compression fitting 1/4" for hose 6x8

CONTROL SYSTEMS AND OPTIONAL DEVICES


Electronica	Basic / Touch
Constant pressure working	Default
Automatic flushing	Default with reduction of RPM motor at 30%*
Safety control	High/low pressure Low voltage

*Not available for 230V


COMPONENTS




CONTROL PANEL (BASIC)
Depth: 3,6 cm
Cut dimensions: 7,6x4,4 cm




CONTROL PANEL (TOUCH)
Depth: 3,2 cm
Cut dimensions: 11x8,8 cm




NON-RETURN VALVE
Depth: 4,7 cm




MESH FILTER GROUP
Depth: 9,1 cm




ACTIVE CARBON FILTER GROUP
Depth: 13,1 cm




5 MICRON FILTER GROUP
Depth: 11,3 cm




PUMP GROUP
Depth: 25,5 cm - Weight: 6,7 kg




PUMP GROUP 230V
Depth: 40,4cm – Weight: 12kg



ELECTRICAL PUMP BOX (BASIC)
Depth: 12,8 cm




COMPUTER BOX (TOUCH)
Depth: 8 cm



WATERMAKER
Depth: 33,6 cm - Weight: 42,2 kg

INSTALLATION SCHEME



- | | |
|---------------------------------|-------------------------|
| 1 Pressurized fresh water valve | 7 Fresh water outlet |
| 2 Electrovalve | 8 Pump |
| 3 5 micron filter | 9 Non return valve |
| 4 Accumulator | 10 Mesh filter |
| 5 Swan neck upwater - Discharge | 11 Sea water inlet |
| 6 Watermaker | 12 Active carbon filter |

SCHENKER ITALIA s.r.l.

Via Ferrante Imparato, 499/501, Condominio Genesis

80146 NAPOLI – NA – Italia

Email: info@schenker.it

Web: <https://schenkerwatermakers.com/>

Tel. +39 0815593505 - 0815590931