


TECHNICAL DATA

Product type	Reverse osmosis watermaker
Application	Seawater for nautical application
Production	65 l/h ±15% (17,7 gal/h ±15%) @35 ppm e 25 °C
Membranes	2x Membrane SW-2521
Rejection	99,5% (nominal)
Power supply	12 V ±15% DC 24 V ±15% DC
Absorption - Power required	25 A ±15% - 300 W ±15% (12 V) 12 A ±15% - 300 W ±15% (24 V)
Pumps	Pompa rotativa
Pressure pump	7,8 – 8,2 bar
Flow rate pump	9,8 – 10,8 l/min
Water inlet temperature range	8 - 30 °C
Pre-filtration	1x 5micron filter 10"x2-1/2" 1x Active carbon filter 2-7/8" x 9-3/4"



HYDRAULIC CONNECTIONS

PUMP / FILTERS / NR VALVE

Seawater inlet	Hose barb DN16
Seawater outlet	Hose barb DN16


WATERMAKER

Seawater inlet	Hose barb DN16
Concentrated water outlet	Hose barb DN16
Fresh water outlet	Compression fitting 1/4" for hose 6x8


CONTROL SYSTEMS AND OPTIONAL DEVICES

Electronica	Basic / Minitouch / Touch
Funzionamento a pressione costante	Standard
Risciacquo automatico	Standard con riduzione del numero di giri del motore del 30%
Monitoraggio salinità permeato	N.A. (Basic) / Optional (Touch)


COMPONENTS




CONTROL PANEL (BASIC)
Depth: 3,2 cm
Cut dimensions: 7,6x4,4 cm




CONTROL PANEL (MINITOUCH)
Depth: 3,2 cm
Cut dimensions: 7,9x5,6 cm




CONTROL PANEL (TOUCH)
Depth: 3,2 cm
Cut dimensions: 11x8,8 cm




NON-RETURN VALVE
Depth: 4,7 cm




MESH FILTER GROUP
Depth: 9,1 cm




ACTIVE CARBON FILTER GROUP
Depth: 13,1 cm




5 MICRON FILTER GROUP
Depth: 11,3 cm




PUMP GROUP
Depth: 25,5 cm - Weight: 6,7 kg




COMPUTER BOX (TOUCH)
Depth: 8 cm



ELECTRICAL PUMP BOX (BASIC)
Depth: 12,8 cm




ELECTRICAL PUMP BOX (TOUCH)
Depth: 9,6 cm



WATERMAKER
Depth: 19,4 cm - Weight: 22,9 kg

INSTALLATION SCHEME



- | | | | |
|---|-------------------------------|----|----------------------|
| 1 | Pressurized fresh water valve | 7 | Fresh water outlet |
| 2 | Electrovalve | 8 | Pump |
| 3 | 5 micron filter | 9 | Non return valve |
| 4 | Accumulator | 10 | Mesh filter |
| 5 | Swan neck upwater - Discharge | 11 | Sea water inlet |
| 6 | Watermaker | 12 | Active carbon filter |

SCENKER ITALIA s.r.l.

Via Ferrante Imparato, 499/501, Condominio Genesis
80146 NAPOLI – NA – Italia

Email: info@schenker.it

Web: <https://schenkerwatermakers.com/>

Tel. +39 0815593505 - 0815590931